

# **Technical Data Sheet**

Rev. A (05/18) Page 1 of 1

### **Turbo-Coat Thinner** Product# 2110

#### **Product Description**

Turbo-Coat Thinner is available to reduce the viscosity to fit ideal process parameters. Turbo-Coat, Turbo-Coat HV, and Turbo-Coat Thinner are all HAPs (Hazardous Air Polutants) free, so do not contain common coating solvents like Toluene, Xylene, and MEK. This makes these coating more user friendly and safe.

#### Features / Benefits

- Compatible with All Turbo-Coat Coatings
- MEK, Toluene & Xylene Free
- Low Toxicity
- Also Used as Stripper & Nozzle Cleaner

#### **Packaging and Availability**

2110-P 1 Pint Liquid 2110-G 1 Gallon Liquid 2110-5G 5 Gallon Liquid

#### **Environmental Policy**


Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

#### **Resources**

Techspray® products are supported by global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



#### **Typical Product Data and Physical Properties**

Physical State:	Liquid
Odor:	Sweet ester odor
Color:	Clear, colorless
Percent Volatile:	100 at 77ºF (25ºC)
Vapor pressure:	9.606 mmHg @ 20ºC
Vapor density:	>1 (Air=1)
Boiling Point:	251ºF (121.7ºC)
Flashpoint and method:	86ºF (30ºC)
Solubility in water:	~48
Evaporation rate:	>1 (n-Butyl Acetate=1)
Density:	0.9 at 68°F (25°C)
VOC:	100% by weight
Shelf life:	5 years unopened; 2 years open



Techspray® 8125 Cobb Center Drive Kennesaw, GA 30152 800-858-4043 tsales@techspray.com

#### Europe

ITW Contamination Control BV Saffierlaan 5, 2132 VZ Hoofddorp The Netherlands +31 88 1307 400 info@itw-cc.com

## Countries outside the US

Call to locate a distributor in your country